

# les greens confort +

**UPEC**  
CSTB  
U3P3E1C0  
04/016



<b>Composition</b>	100% Polyamide
Pile material	100% Nylon
Polmaterial	100% Polyamid
Poolmateriaal	100% Polyamide
Composición	100% Poliamida
Composizione	100% Poliammide
Skład runa	100% Poliamid

<b>Poids de velours / Pile weight / Poleinsatzgewicht / Poolinzetmassa / Peso fibra / Peso felpa / Gramatura</b>	700 g/m <sup>2</sup>
--	----------------------

<b>Poids total - NF ISO 8543 / Total weight / Gesamtgewicht / Totaal gewicht / Peso total / Peso totale / Masa całkowita</b>	1 900 g/m <sup>2</sup>
--	------------------------

<b>Epaisseur totale - NF ISO 1765 / Total thickness / Gesamtdicke / Totale massa / Altura total / Spessore totale / Wysokość całkowita</b>	9,2 mm
--	--------


<b>Hauteur du velours - NF ISO 1766 / Pile height / Polhöhe / Poolhoogte / Altura fibra / Spessore felpa / Wysokość runa</b>	5,7 mm
--	--------

<b>Envers / Backing / Rückenausstattung / Rug / Soporte / Sottofondo / Podklad</b>	Double dossier feutre Confort + / Feltback confort +
--	---

<b>Jauge - Serrage (points) - Densité - NF ISO 1763</b>	5/64 <sup>e</sup>
Gauge - Rows (points) - Tufts	74 p
Teilung - Stiche (points) - Noppenzahl	370 000 p/m <sup>2</sup>
Rijen - Deling (points) - Noppenaantal	
Galga - Densidad (puntos)	
Scartamento - Serraggio (punti) - Densità felpa	
Zacześnieenie - Rozstaw igiel (punkty) - Gęstość	

<b>Comportement au feu Cfl-s1 - collé sur ciment</b>	Cfl-s1 - collé sur ciment
Fire resistance	Cfl-s1 - glued on cement
Brennverhalten	Cfl-s1 - geklebt auf Zement
Brandgedrag	Cfl-s1 - verlijmd op cement
Clasificación al fuego	Cfl-s1 - pegado en cemento
Comportamento al fuoco	Cfl-s1 - incollato su cemento
Trudnozupalność	Cfl-s1 - klejone na podłożu betonowym

**HQE Ce produit répond parfaitement à 8 des 14 cibles**  
 HQE This product meets perfectly 8 from the 14 targets  
 HQE Dieses Produkt erfüllt 8 von den 14 Zielen  
 HQE Dit product beantwoordt aan 8 van de 14 doelstellingen  
 HQE Este producto responde perfectamente a 8 de los 14 objetivos  
 HQE Questo prodotto risponde perfettamente a 8 di 14 target  
 HQE Ten produkt odpowiada 8 z 14 kryteriów



<b>Absorption aux bruits aériens - NF EN ISO 11654</b>	
Sound absorption / Schallabsorptionsgrad / Geluidsabsorptie / Absorción de los ruidos aéreos / Isolazione acustica / Pochťanianie dźwięku	αw 0,35
<b>f/Hz</b>	125 250 500 1000 2000 4000
<b>αs</b>	0,03 0,05 0,27 0,35 0,43 0,55

<b>Pose / Entretien / Traitement</b>	
Laying / Cleaning / Treatment	
Verlegelinweis / Reinigung / Behandlung	
Plaatsinstructie / Reiniging / Onderhoud	www.balsan.com
Instalación / Mantenimiento / Tratamiento	
Posa / Manutenzione / Trattamenti	
Układanie / Utrzymanie w czystości / Impregnacja	

BALSAN se réserve le droit de modifier les caractéristiques de ce produit tout en conservant les mêmes qualités techniques. Dans le cadre d'une utilisation professionnelle, il est fortement conseillé d'utiliser des coloris moyens et foncés pour les pièces à grand trafic. De légères variations de coloris peuvent être observées entre les différents bains de teinture. In the context of business use, we strongly recommend the use of darker colours for heavy traffic areas. Slight differences in colour may occur between different dye baths.



Designed and Made in France





wall to wall

UNIS



wall to wall

DESIGN



custom



modular



CAHIER TECHNIQUE  
TECHNICAL HANDBOOK





Armure 918 4 + 5 m



Perle 940 4 m



Lièvre 733 4 + 5 m



Givre 900 4 m



Nacre 003 4 m



Mercure 945 4 m



Étain 948 4 + 5 m



Sépia 758 4 + 5 m



Loup 710 4 m



Érable 010 4 + 5 m



Onyx 975 4 m



Cendre 955 4 m



Taupe 775 4 + 5 m



Faon 738 4 m



Chaume 615 4 + 5 m



Charbon 988 4 + 5 m



Fusain 780 4 m



Cannelle 760 4 m



Garrigue 630 4 + 5 m



Ébène 999 4 m



Bois 795 4 m



Écaille 768 4 + 5 m



Daim 348 4 m



Arabica 790 4 m



Caramel 660 4 m



				
Azur 130 4 m	Ambre 320 4 m	Argile 720 4 m	Potiron 568 4 m	Fuchsia 550 4 m
				
Céleste 138 4 + 5 m	Lemon 210 4 m	Thuya 740 4 m	Capucine 560 4 m	Pomone 585 4 m
				
Saxe 188 4 m	Tilleul 238 4 m	Parme 830 4 m	Églantine 570 4 m	Sève 595 4 m
				
Nuit 195 4 m	Jungle 280 4 m	Pourpre 868 4 m	Opéra 563 4 + 5 m	
				
Évêque 878 4 m	Loden 285 4 m	Bordeaux 598 4 m	Châtaignier 480 4 m	
				
Prune 885 4 m	Océan 150 4 m			



wall to wall

UNIS



wall to wall

DESIGN



custom



modular



CAHIER TECHNIQUE  
TECHNICAL HANDBOOK