



**UPEC**  
CSTB  
U3P3E1C0  
08/254



**Composition** 100% Polyamide  
*Pile material* 100% Nylon  
*Polmaterial* 100% Polyamid  
*Poolmateriaal* 100% Polyamide  
*Composición* 100% Poliamida  
*Composizione* 100% Poliammide  
*Sklad runa* 100% Poliamid

**Poids de velours / Pile weight /**  
*Poleinsatzgewicht / Poolinzetmassa /* 1 040 g/m<sup>2</sup>  
*Peso fibra / Peso felpa / Gramatura*

**Poids total - NF ISO 8543 / Total weight /**  
*Gesamtgewicht / Totaal gewicht /* 1 970 g/m<sup>2</sup>  
*Peso total / Peso totale / Masa całkowita*

**Épaisseur totale - NF ISO 1765 /**  
*Total thickness / Gesamtdicke /* 6,8 mm  
*Totale massa / Altura total /*  
*Spessore totale / Wysokość całkowita*

**Hauteur du velours - NF ISO 1766 /**  
*Pile height / Polhöhe / Poolhoogte /* 4,6 mm  
*Altura fibra / Spessore felpa / Wysokość runa*

**Envers / Backing /**  
*Rückenausstattung / Rug /* Double dossier /  
*Soporte / Sottofondo / Podklad* Action back

**Jauge - Serrage (points) - Densité - NF ISO 1763**  
*Gauge - Rows (points) - Tufts*  
*Teilung - Stiche (points) - Noppenzahl* 1/10<sup>e</sup>  
*Rijen - Deling (points) - Noppenaantal* 52 p  
*Galga - Densidad (puntos)* 205 400 p/m<sup>2</sup>

**Comportement au feu Cfl-s1 - collé sur ciment**  
*Fire resistance Cfl-s1 - glued on cement*  
*Brennverhalten Cfl-s1 - geklebt auf Zement*  
*Brandgedrag Cfl-s1 - verlijmd op cement*  
*Clasificación al fuego Cfl-s1 - pegado en cemento*  
*Comportamento al fuoco Cfl-s1 - incollato su cemento*  
*Trudnozupalność Cfl-s1 - klejone na podłożu betonowym*

**HQE Ce produit répond parfaitement à 8 des 14 cible**  
*HQE This product meets perfectly 8 from the 14 targets*  
*HQE Dieses Produkt erfüllt 8 von den 14 Zielen*  
*HQE Dit product beantwoordt aan 8 van de 14 doelstellingen*  
*HQE Este producto responde perfectamente a 8 de los 14 objetivos*  
*HQE Questo prodotto risponde perfettamente a 8 di 14 target*  
*HQE Ten produkt odpowiada 8 z 14 kryteriów*



**Absorption aux bruits aériens - NF EN ISO 11654**  
*Sound absorption / Schallabsorptionsgrad /*  
*Geluidsabsorptie / Absorción de los ruidos* αw 0,20  
*aéeros / Isolazione acustica /*  
*Pochłanianie dźwięku*

f/Hz	125	250	500	1000	2000	4000
αs	0,01	0,03	0,09	0,25	0,37	0,47

**Pose / Entretien / Traitement**  
*Laying / Cleaning / Treatment*  
*Verlegelinweis / Reinigung / Behandlung*  
*Plaatsinstructie / Reiniging / Onderhoud* www.balsan.com  
*Instalación / Mantenimiento / Tratamiento*  
*Posa / Manutenzione / Trattamenti*  
*Układanie / Utrzymanie w czystości / Impregnacja*

BALSAN se réserve le droit de modifier les caractéristiques de ce produit tout en conservant les mêmes qualités techniques. Dans le cadre d'une utilisation professionnelle, il est fortement conseillé d'utiliser des coloris moyens et foncés pour les pièces à grand trafic. De légères variations de coloris peuvent être observées entre les différents bains de teinture. / BALSAN reserves the right to modify the characteristics of this product while keeping the same technical properties. In the context of business use, we strongly recommend the use of darker colours for heavy traffic areas. Slight differences in colour may occur between different dye baths.



Designed and Made in France



Sésame 720 4 m



Champagne 605 4 m



Taupe 760 4 m



Or 380 4 m



Daim 620 4 m



Argent 910 4 m



Absinthe 240 4 m



Cuivre 450 4 m



Zinc 930 4 m



Jade 250 4 m



Brique 470 4 m



Rubis 570 4 m



Carbone 990 4 m



Outremer 160 4 m



Moka 730 4 m



Cassis 580 4 m



Anthracite 995 4 m



Encre 180 4 m



Muscade 790 4 m



Bourgogne 590 4 m



Absinthe 240

bonding with the world



wall to wall

UNIS



wall to wall

DESIGN



custom



modular



CAHIER TECHNIQUE  
TECHNICAL HANDBOOK

