

 sydney DD

**UPEC**  
CSTB  
U3P3E1C0  
04/060



**Composition** 100% Polyamide  
*Pile material* 100% Nylon  
*Polmaterial* 100% Polyamid  
*Poolmateriaal* 100% Polyamide  
*Composición* 100% Poliamida  
*Composizione* 100% Poliammide  
*Skład runa* 100% Poliamid

**Poids de velours / Pile weight /**  
*Poleinsatzgewicht / Poolinzetmassa /* 650 g/m<sup>2</sup>  
*Peso fibra / Peso felpa / Gramatura*

**Poids total - NF ISO 8543 / Total weight /**  
*Gesamtgewicht / Totaal gewicht /* 1650 g/m<sup>2</sup>  
*Peso total / Peso totale / Masa całkowita*

**Épaisseur totale - NF ISO 1765 /**  
*Total thickness / Gesamtdicke /* 7 mm  
*Totale massa / Altura total /*  
*Spessore totale / Wysokość całkowita*

**Hauteur du velours - NF ISO 1766 /**  
*Pile height / Polhöhe / Poolhoogte /* 4,8 mm  
*Altura fibra / Spessore felpa / Wysokość runa*

**Envers / Backing /**  
*Rückenausstattung / Rug /* Double dossier /  
*Soporte / Sottofondo / Podkład* Action back

**Jauge - Serrage (points) - Densité - NF ISO 1763**  
*Gauge - Rows (points) - Tufts* 1/10<sup>e</sup>  
*Teilung - Stiche (points) - Noppenzahl* 60 p  
*Rijen - Deling (points) - Noppenaantal* 237 000 p/m<sup>2</sup>  
*Galga - Densidad (puntos)*  
*Scartamento - Serraggio (punti) - Densità felpa*  
*Zaciesnienie - Rozstaw igiel (punkty) - Gęstość*

**Comportement au feu Cfl-s1 - collé sur ciment**  
*Fire resistance* Cfl-s1 - glued on cement  
*Brennverhalten* Cfl-s1 - geklebt auf Zement  
*Brandgedrag* Cfl-s1 - verlijmd op cement  
*Clasificación al fuego* Cfl-s1 - pegado en cemento  
*Comportamento al fuoco* Cfl-s1 - incollato su cemento  
*Trudnozupalność* Cfl-s1 - klejone na podłożu betonowym

**HQE Ce produit répond parfaitement à 8 des 14 cibles**  
*HQE This product meets perfectly 8 from the 14 targets*  
*HQE Dieses Produkt erfüllt 8 von den 14 Zielen*  
*HQE Dit product beantwoordt aan 8 van de 14 doelstellingen*  
*HQE Este producto responde perfectamente a 8 de los 14 objetivos*  
*HQE Questo prodotto risponde perfettamente a 8 di 14 target*  
*HQE Ten produkt odpowiada 8 z 14 kryteriów*



*Balsan*  
protect  
www.balsan.com/balsanprotect



**Pose / Entretien / Traitement**  
*Laying / Cleaning / Treatment*  
*Verlegehinweis / Reinigung / Behandlung*  
*Plaatsinstructie / Reiniging / Onderhoud* www.balsan.com  
*Instalación / Mantenimiento / Tratamiento*  
*Posa / Manutenzione / Trattamenti*  
*Układanie / Utrzymanie w czystości / Impregnacja*

BALSAN se réserve le droit de modifier les caractéristiques de ce produit tout en conservant les mêmes qualités techniques. Dans le cadre d'une utilisation professionnelle, il est fortement conseillé d'utiliser des coloris moyens et foncés pour les pièces à grand trafic. De légères variations de coloris peuvent être observées entre les différents bains de teinture. / BALSAN reserves the right to modify the characteristics of this product while keeping the same technical properties. In the context of business use, we strongly recommend the use of darker colours for heavy traffic areas. Slight differences in colour may occur between different dye baths.



Institut Pasteur  
BALSAN QUALITY EXCELLENCE PARTNER  
www.balsan.com/pasteur



Designed and Made in France





wall to wall

UNIS



wall to wall

DESIGN



custom



modular





Praline 530 4 m



Pêche 440 4 m



Saumon 410 4 m



Crème 605 4 m



Neige 003 4 m




Pivoine 560 4 m




Paprika 550 4 m



Tango 450 4 m



Noisette 740 4 m



Dune 615 4 m



Pourpre 590 4 m



Rubis 570 4 m



Argile 750 4 m



Melon 460 4 m



Cannelle 640 4 m



Prune 890 4 m




Bordeaux 580 4 m



Renard 490 4 m























Daim 680 4 m



Castor 690 4 m



				
Lichen 210 4 m	Aqua 125 4 m	Azur 130 4 m	Nuage 910 4 m	Angora 706 4 m
				
Amande 220 4 m	Hawaï 255 4 m	Cobalt 160 4 m	Mistigri 940 4 m	Ourson 780 4 m
				
Mousse 240 4 m	Véronèse 265 4 m	Pétrole 190 4 m	Ardoise 980 4 m	Taupe 770 4 m
				
Mélèze 245 4 m	Cèdre 280 4 m	Marine 199 4 m	Noir 990 4 m	Chocolat 790 4 m



wall to wall

UNIS



wall to wall

DESIGN



custom



modular



CAHIER TECHNIQUE  
TECHNICAL HANDBOOK